

COMFORT

Quiet Operation

By optimizing the design of fan motor, air duct and heat exchanger, the new duct operates with noise as low as 22dB(A), creating a quieter and more comfortable environment.






- > Fan motor noise reduction
- > Air duct noise reduction
- > Heat exchanger noise reduction

Two thermistors control

The indoor temperature can be checked using the thermistor in the wried controller as well as from the indoor unit



Auto Cooling-heating Changeover

Automatically selects cooling or heating mode to achieve the set temperature.



AIR FLOW

Constant Airflow

Constant airflow technology can realize the airflow output is not affected by installation conditions and use conditions, ensuring the constant airflow supply.







HEALTH

Healthy Air Supply

The Arc Duct unit adopts an integrated C-shaped heat exchanger that allows for fast drainage and no dust or ash accumulation. The optional long-life filter, medium-life filter and plasma sterilization module further enhance the air quality of the air supply and create a healthy environment.





Silver lons drain pan (optional)

Slow-released nano-silver ions can keep the drain pan free of mold for a long time.




Conventional V-shaped heat exchanger Integrated C-shaped heat exchanger VS Folded seam hide dirt and grime Fast drainage without adhesion



EASY INSTALLATION

Ultra-thin Body

Ultra-thin body design, the body height of the whole series is only 199mm, greatly saving space and more flexible installation.



High-lift drain pump

A drain pump with a 1200mm raise height is fitted as standard, simplifying installation of the drain piping.



Fault Feedback

Early warning of drain pump fault.

